

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **04265124 A**

(43) Date of publication of application: **21.09.92**

(51) Int. Cl.

B01D 53/36

B01D 53/30

B01D 53/34

(21) Application number: **03047418**

(22) Date of filing: **21.02.91**

(71) Applicant: **SUMITOMO CHEM ENG
KKSakai CHEM IND CO LTD**

(72) Inventor: **SAKAMOTO TOKUO
AIDA NOBUHITO
RIKIMARU HIROAKI
OKOCHI TSUTOMU
YOSHIDA JIRO**

(54) DENITRATION METHOD

(57) Abstract:

PURPOSE: To excellently denitrate a gas even if the concn. of nitrogen oxides in the gas is largely and rapidly changed.

CONSTITUTION: The value SV for the concn. of nitrogen oxides at the outlet of a reactor giving a specified denitration efficiency is calculated. When the measured value PV for the concn. of nitrogen oxides at the outlet of the reactor is lower than the SV, the stoichiometric flow rate B of ammonia necessary to reduce the nitrogen oxides supplied to the reactor minus a specified flow rate Δ , i.e., $(B - \Delta)$, is supplied to the reactor, and the stoichiometric flow rate of ammonia plus the specified flow rate, i.e., $(B + \Delta)$, is supplied for a fixed time T after the PV exceeds the SV.

COPYRIGHT: (C)1992,JPO&Japio

